




Installation Method



Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Barricade Two **Colour** Grey **Collection** Barricade Collection **Backing** CQuest™Bio

Product Specifications

Product Construction	Tufted Plain Textured Loop Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
Size	50cm x 50cm
Tiles per Box	16 - 4m ²

More Product Specifications

Pile Yarn Weight	726 g/m ² ± 5%
Total Weight	4,005 g/m ² ± 5%
Pile Height	3.6 mm +15% / - 10%
Total Thickness	6.7 mm ±0.5mm
Gauge - Ends per 10 cm	5/32 - 25.2
Tufts per m ²	100800 /m ² ±5%















Performance Specifications

Wear Classification	EN 1307 32 General Contract
Castor Chair Rating	≥2.0 (EN 985) Occasional Use
Flammability	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1) Bfl-s1 on request
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	24.60
Light Reflectance Value (LRV-Y)	4.30
Dimensional Stability	≤0.2% (ISO 2551/EN 986)

Environmental Specifications

Environmental Product Declaration	Download EPD
Total Recycled Content	82.5 %
Pre-Consumer (Total)	73.00 %
Post-Consumer (Total)	9.50 %
Yarn Recycled Content	100.00 %
Pre-Consumer (Yarn)	50.00 %
Post-Consumer (Yarn)	50.00 %
Total Bio Based Content	9.46 %
Total Recycled & Bio Based Content	91.96 %
Indoor Air Quality	French A+ GLP 100209
Indoor Air Quality GUI	GUI Standard
HQE (France)	View Potential HQE Contribution
DGNB (Germany)	View Potential DGNB Contribution
Embodied Carbon (Cradle to Gate)	3.43 kg CO ₂ eq./m ²
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
Installation Waste	Monolithic - 3-4%
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
Technical Information	
Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	7 years
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe

Certifications

 <p>DOP: 1037/125749 EN 14041:2004 Notified Body - 0493 COC 0493 - CFR - 0181 For use as floor covering in buildings</p>	4200C
 <p>DOP: 1037/125749 EN 14041:2004 Approved Body - 0321 COC 0321/20664-02/E00-00 For use as floor covering in buildings</p>	4200C
	EN 1307 32 General Contract
	LC2
	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)
	Yes
	Yes
	≥ 7
	≤0.2% (ISO 2551/EN 986)
	0.10
	≥2.0
	GUI Standard
	French A+
	4200C