




AMARON FORMA



6,3 / 1,3 / 0,55 mm

914 mm 457 mm

1 BOX = 5  = 2,088 m²

10 dB Δ Lin
20 dB

ACULAY
INTEGRATED
ACOUSTIC UNDERLAY

HD
HD MINERAL
CORE

5G
CROSS
Licensed by
Välinge

**ANTI-
SCRATCH**
TITANIUM
NANO-LAYER

UNDERFLOOR
HEATING

100%
WATERPROOF

UP TO 200 m²
WITHOUT
DILATATION

SILENT
FLOOR

PRODUCT SPECIFICATION



VALUE

Floor type	Click floor with acoustic layer
Dimensions	914 x 457 mm
Total thickness	5,0 + 1,3 mm
Wear layer thickness	0,55 mm
Quantity of panels in the package	5 pcs (2,088 m ²)
Quantity of package in the pallet	38 pcs (79,344 m ²)
Warranty (the household indoor use)	25 years
Installation	Click: 5G Cross Välinge
CE	EN 14041:2004/ AC:2006
DoP	RF50055/20
Customs tariff number	39181090

TECHNICAL PARAMETERS

NORM

VALUE

Class of use RESIDENTIAL	EN ISO 10874	23 (hall, kitchen, living room, dining room)
Class of use COMMERCIAL	EN ISO 10874	33 (shopping centres, schools, large-area offices, halls)
Class of use INDUSTRIAL	EN ISO 10874	42 (storage rooms, workshops)
Reaction to fire	EN 14041 (EN 13501)	Bfl-s1
Dimensional stability	EN ISO 23999	≤0,05% (norm ≤0,25%)
Wear resistance	EN 13329 Annex E	≥7000 (norm ≥2000)
Residual indentation	EN ISO 24343-1	≤0,02 mm (norm ≤0,10 mm)
Castor chair resistance	ISO 4918	Type W >25000 cycles (no damage on wear layer, no stratification)
Resistance to large ball	ISO 24334	1800 mm (norm 1600 mm)
Locking strength	EN ISO 10582 Annex D	long edge 5,2 kN/m, short edge 6,5 kN/m
Slip resistance	EN 13893 / DIN 51130	DS/R9
Antistatic and electrical properties	EN 14041 (EN 1815)	<2kV
Resistance to stain and chemicals	EN ISO 26987	INDEX 0 (very good)
Light fastness	EN ISO 105-B02	≥6
Thermal resistance	EN 12667	0,042 m ² k/W
Underfloor heating	EN 12524	yes (max 27°C)
IS - Impact sound improvement (integrated acoustic underlay)	EN ISO 717-2	ΔLw = 20 dB
Formaldehyde emission	EN 717-1	Class E1
Substances of Very High Concern	EN 717-1	SVHC free
VOC		A+

LOGISTIC PARAMETERS

	Packaging Unit	Pallet
Form	Box (2,088 m ²)	79,344 m ²
Weight	22,07 kg +/- 10%	870 kg +/- 10%
Sizes	926 x 468 x 35 mm	960 x 980 x 815 mm

CE

25

Decora S.A.
Ignacego Prądzyńskiego 24a
63-000 Środa Wielkopolska

RF50055/20

**EN 14041:2004
1021**

Floor coverings for interior use

React on to fire	B _{fl} -s1
Slip resistance	DS
Formaldehyde emission	E1

OTHER

