




Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Touch Of Timber **Colour** Oak **Backing** CQuest™Bio

Product Specifications

| | |
|----------------------|-------------------------------------|
| Product Construction | Microtuft Patterned Level Loop Pile |
| Yarn System | 100% Recycled Solution Dyed Nylon |
| Standard Backing | CQuest™Bio |
| Size | 25cm x 1m |
| Tiles per Box | 20 - 5m ² |

More Product Specifications

| | |
|--------------------------|-----------------------------|
| Pile Yarn Weight | 499 g/m ² ± 5% |
| Total Weight | 3,939 g/m ² ± 5% |
| Total Thickness | 5 mm ±0.5mm |
| Gauge - Ends per 10 cm | 5/64 - 50.4 |
| Tufts per m ² | 186480 /m ² ±5% |

Performance Specifications

| | |
|--|---|
| Wear Classification | EN 1307 33 Heavy Contract |
| Castor Chair Rating | ≥2.4 (EN 985) Continuous Use |
| Flammability | (EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1) |
| Light Fastness | ≥7 (ISO 105-B02) |
| Light Reflectance Value (LRV-L) | 57.30 |
| Light Reflectance Value (LRV-Y) | 25.20 |
| Dimensional Stability | ≤0.2% (ISO 2551/EN 986) |
| Impact Sound Insulation ΔLw EN ISO 10140-3 | 16 dB |
| Rating of Sound Absorption (αw) EN ISO 11654 | 0.15 |
| Sound Absorption (αs)EN ISO 354 at 125 Hz | 0.01 |
| Sound Absorption (αs)EN ISO 354 at 250 Hz | 0.01 |
| Sound Absorption (αs)EN ISO 354 at 500 Hz | 0.06 |
| Sound Absorption (αs)EN ISO 354 at 1000 Hz | 0.14 |
| Sound Absorption (αs)EN ISO 354 at 2000 Hz | 0.25 |
| Sound Absorption (αs)EN ISO 354 at 4000 Hz | 0.33 |

Environmental Specifications











| | |
|------------------------------------|--|
| Environmental Product Declaration | Download EPD |
| Total Recycled Content | 82 % |
| Pre-Consumer (Total) | 76.00 % |
| Post-Consumer (Total) | 6.00 % |
| Yarn Recycled Content | 100.00 % |
| Pre-Consumer (Yarn) | 50.00 % |
| Post-Consumer (Yarn) | 50.00 % |
| Total Bio Based Content | 9.6 % |
| Total Recycled & Bio Based Content | 92.2 % |
| Indoor Air Quality | French A+ |
| HQE (France) | View Potential HQE Contribution |
| DGNB (Germany) | View Potential DGNB Contribution |

| | |
|----------------------------------|---|
| Embodied Carbon (Cradle to Gate) | 2.84 kg CO ₂ eq./m ² |
| Full Life Cycle Carbon | Certified Carbon Neutral Floors™ |
| Installation Waste | Herringbone 3-5% Ashlar – 3-5 % |
| TacTiles® | Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs |
| Recycling | Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles. |
| ReUse | Can be cleaned and reused in a non-critical location to extend its useful life. |
| Waste to Energy | Can be incinerated in appropriate waste to energy plant. |

Technical Information

| | |
|------------------------|--|
| Installation | See recommended Interface installation guidelines |
| Maintenance | See recommended Interface maintenance guidelines |
| Warranty | 15 years |
| Manufacturing Location | ISO 9001, 14001 & 45001 Certified Facilities in Europe |

Certifications

| | |
|---|---|
|  | 4191C |
|  | 4191C |
|  | EN 1307 33 Heavy Contract |
|  | LC1 |
|  | (EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1) |
|  | Yes |
|  | Yes |
|  | 16 dB |
|  | 0.15 |
|  | ≥ 7 |
| ≤0.2% (ISO 2551/EN 986) | |



0.03

≥2.4

Yes

French A+

4191C