24 hours water resistant

water resistant laminate floors

WAVE herringbone


Technical data

AC5

plank dimensions mm	504 x 84 mm
plank thickness mm	8 mm
bevels	4
loc system	angle-snap loc system
level of use according EN 10874	23 heavy domestic use / 32 general commercial use
composition	top: direct laminated paper, impregnated with melamine resin core: moisture resistant high density fiberboard (HDF), treated with a water repelling coating backing: direct laminated paper, impregnated with melamine resin
1 pack	24 planks - 1,02 m² - 7,3 kg
1 pallet	48 packs - 48,77 m² - 365 kg
residential warranty	20 years
commercial warranty	3 years

abrasion resistance	ISO 24338 A	AC5 (IP ≥6000)
impact resistance	EN 17368/EN 13329	small ball : ≥ 35 mm - big ball : ≥ 600 mm
thickness swelling	ISO 24336	12% (requirement ≤ 15%)
fire resistance	EN 13501-1	Cfl-S1
formaldehyde emission	EN 717-1	E1
slip resistance	EN 13893	DS
density	EN 323	900 kg/m³
resistance to staining	EN 438	5 (group 1+2) ; 4 (group 3)
effect of a furniture leg	EN ISO 16581	no damage (foot type 0)
effect of a castor chair	EN ISO 4918	no damage with type W wheels, 15.000 cycles
thermal resistance	ISO 8302	0,06 m².K/W Suitable for floor heating/cooling. Detailed instructions on www.waterresistantlaminate.org.

What is a laminate floor made of?



1. An overlay that determines the strength and resistance of your floor.
2. A decor paper for the design.
3. A high-density fibreboard (HDF) core.
4. A counterbalance to stabilise and protect the HDF core.
5. A water-repellent coating.

EN 14041
CE 23 DOP 170-DPLA23-1 | UK CA 23 DOC UK 170-DPLA23-1
Berryalloc NV
Industrielaan 100
8930 Menen, Belgium
NB 1161
Laminate floor covering for use within building
www.berryalloc.com

PEFC Certified
laminate flooring from sustainably managed forests and controlled sources
PEFC
PEFC/07-31-229
www.pefc.be

ÉMISSIONS DANS L'AIR INTÉRIEUR*
A
A+ A B C
*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

EUROPEAN LAMINATE EPLF MADE WITH WOOD