


**Installation Method**



Quarter turn

Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Heuga 580 II **Colour** Laurel **Backing** CQuest™Bio

**Product Specifications**

Product Construction	Tufted Plain Level Loop Pile
Yarn System	100% Recycled Nylon
Standard Backing	CQuest™Bio
Size	50cm x 50cm
Tiles per Box	20 - 5m <sup>2</sup>
Optional Backings	<a href="#">CQuest™Bio SONE</a>

**More Product Specifications**

Pile Yarn Weight	580 g/m <sup>2</sup> ± 5%
Total Weight	3,789 g/m <sup>2</sup> ± 5%
Pile Height	2.7 mm +15% / - 10%
Total Thickness	5.8 mm ±0.5mm
Gauge - Ends per 10 cm	1/10 - 39.4
Tufts per m <sup>2</sup>	160,690 /m <sup>2</sup> ±5%

**Performance Specifications**

Wear Classification	EN 1307 33 Heavy Contract
Castor Chair Rating	≥2.4 (EN 985) Continuous Use
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥5 (ISO 105-B02)
Light Reflectance Value (LRV-L)	47.40
Light Reflectance Value (LRV-Y)	16.40
Dimensional Stability	≤0.2% (ISO 2551/EN 986)
Impact Sound	25 dB
Insulation ΔLw EN ISO 10140-3	
Rating of Sound Absorption (αw) EN ISO 11654	0.15
Sound Absorption (αs)EN ISO 354 at 125 Hz	0.02
Sound Absorption (αs)EN ISO 354 at 250 Hz	0.03
Sound Absorption (αs)EN ISO 354 at 500 Hz	0.06
Sound Absorption (αs)EN ISO 354 at 1000 Hz	0.17
Sound Absorption (αs)EN ISO 354 at 2000 Hz	0.26
Sound Absorption (αs)EN ISO 354 at 4000 Hz	0.34

**Environmental Specifications**















Environmental Product Declaration	<a href="#">Download EPD</a>
Total Recycled Content	77 %
Pre-Consumer (Total)	69,30 %
Post-Consumer (Total)	7.70 %
Yarn Recycled Content	100.00 %
Pre-Consumer (Yarn)	50.00 %
Post-Consumer (Yarn)	50.00 %
Total Bio Based Content	10.8 %
Total Recycled & Bio Based Content	87.8 %
Indoor Air Quality	<a href="#">Compliant with LEED EQ 5.0 credit</a> French A+ GLP 100254 <a href="#">M1 Emission Certification -CQB</a>
HQE (France)	<a href="#">View Potential HQE Contribution</a>

DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>
Embodied Carbon (Cradle to Gate)	3.53 kg CO <sub>2</sub> eq./m <sup>2</sup>
Installation Waste	Quarter turn – 3-4% Monolithic – 3-4%
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

#### Technical Information

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe

#### Certifications

 DOP: 1037/127624 EN 14041:2004 Notified Body - 0483 COC 0483 - CPR - 0181 For use as floor covering in buildings	 DOP: 1037/127624 EN 14041:2004 Approved Body - 5015 COC 8515/CPR/0181 For use as floor covering in buildings				
		 25 dB	 0.15	 ≥ 5	
 0.07	 ≥2.4	