

Produktbeskrivelse	Metode	Produktdata
Konstruktion		
Struktur	ISO 2424	Tuftet loop pile
Gauge	ISO 2424	3/16
Luvmateriale	DIR 96/73, 96/74	100% uld
Farvemethode	-	Fiberfarvet
Bagside	ETL	XL - Extra high foam
Dimensioner	ISO 3018	Approx. 400/500 cm
Totalhøjde	ISO 1765	Ca. 12,5 mm.
Slidlag	ISO 1766	Ca. 4,5 mm.
Noppeantal	ISO 1763	Ca. 44.000 pr.m2
Totalvægt	ISO 8543	Ca. 3.500 g/m2
Luvindsatsvægt	ETL	1.250 g/m2
Luvmasse	ISO 8543.	Ca. 740 g/m2
Luvdensitet	ISO 8543.	Ca. 0,106 g/cm3
Egnethedsprøvnings		
Antistatiske egenskaber	ETL	Permanent antistatisk
Lysægthed	ISO 105-B02	6
Gnideægthed tør	ISO 105-X12	4-5
Vandægthed ensfarvede	ISO 105-E01	5
Sikkerhed & Miljø		
Brandklassifikation	EN 14041	Efl
	BS EN 14041	Efl
CE Mærkning	EN 14041	Certificeret
	Ydeevnedeklaration	DOP E
	Notified body no.	NA
	Ce Year	18
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
Vejledninger		
Montering, inkl. limguide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Français
Rengøring, pletfjerning	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Français
Producent		
Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK



THE URGE TO EXPLORE SPACE